

BY SOLAX

**TRIPLE**  
POWER

NEW FROM SOLAX

**T-BAT-SYS-LV D53**



**T-BAT-SYS-LV D53**



## Features

### Flexibility

- Modular design, expandable to 16 units in parallel, max. 85kWh capacity
- Available in wall-mounted or floor-mounted options

### High Performance

- Automotive-grade communication for exceptional hardware performance
- Adaptive cut-off enables continuous operation in parallel, even if any battery fails

### Smart Management

- AI-Driven real-time monitoring for minimized system risk
- AI-Driven intelligent algorithms ensure high SOC and accuracy
- AI-Driven battery fault diagnosis for accurate detection

### User Friendly

- Continuous remote OTA one-click upgrades

### Safe and Durable

- Cobalt-Free LFP battery: safer, long-lasting, efficient, high energy density

info@solaxpower.com  
service@solaxpower.com



For more information, please contact us

www.solaxpower.com

AU: +61 1300 476529

DE: +49 6142 4091664

Global: +86 571-56260008

UK: +44 2476 586998

NL: +31 (0) 852 737932

## T-BAT-SYS-LV D53

System Parameters	T-BAT LD53	T-BAT LD106	T-BAT LD159	T-BAT LD212	T-BAT LD265	T-BAT LD318	T-BAT LD371	T-BAT LD424
Number of Module Serie	1	2	3	4	5	6	7	8
Nominal Capacity [kWh]	5.3	10.6	15.9	21.2	26.6	31.9	37.2	42.5
Usable Capacity (90% DOD) <sup>①</sup> [kWh]	4.7	9.5	14.3	19.1	23.9	28.7	33.5	38.3
Max. Output Current [A] <sup>②</sup>	100				120			
Peak Discharge Current [A, s]	200, 10							

System Parameters	T-BAT LD477	T-BAT LD530	T-BAT LD583	T-BAT LD636	T-BAT LD689	T-BAT LD742	T-BAT LD795	T-BAT LD848
Number of Module Serie	9	10	11	12	13	14	15	16
Nominal Capacity [kWh]	47.9	53.2	58.5	63.8	69.2	74.5	79.8	85.1
Usable Capacity (90% DOD) <sup>①</sup> [kWh]	43.1	47.9	52.7	57.5	62.3	67.0	71.8	76.6
Max. Output Current [A] <sup>②</sup>	120							
Peak Discharge Current [A, s]	200, 10							

General Information	
Weight [kg]	48.5
Dimension (L x W x H) [mm]	645 x 150 x 430
Nominal Voltage [V]	51.2
Operating Voltage Range [V]	45 to 58
Battery Type	Lithium Iron Phosphate
Communication Port	CAN / RS485
Operation Temperature [°C]	0 to 53 (charge) ; -20 to 53 (discharge)
Storage Temperature [°C]	30 to 50 (6 months) ; -20 to 30 (12 months)
Ingress Protection	IP65
Colling concept	Natural
Relative humidity [%]	5 to 95 (Non-condensing)
Altitude [m]	< 3000
Warranty <sup>④</sup> [years]	10
Cycle Life <sup>③</sup> [90% DOD]	> 6000
Certification	IEC62619, IEC62040, CE, UN38.3

① Test conditions: 90% DOD, 0.2C charge & discharge @+25 °C

② Current is affected by the number of batteries connected in parallel as well as temperature and SOC

③ 25°C ± 2°C, 0.5C / 0.5C, 70 % EOL > 6000

④ The warranty is due whichever reached first of warranty period or energy throughput